

CAUTIONS

Contains: Petroleum Distillates

INGREDIENTS (C.A.S. #): Petroleum Asphalt (8052-42-4), Mineral Spirits (8052-41-3), Calcium Carbonate (1317-65-3), Attapulgitic Clay (12174-11-7), Cellulose (9004-34-6), and Butyl Rubber (9010-85-9).

VAPOR HARMFUL. MAY EFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION.

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks, and flame. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling and before eating or smoking.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately. In case of skin contact, wash with waterless hand cleaner. If skin is irritated or a rash develops, get medical attention. If swallowed, do not induce vomiting. Call physician immediately.

FOR SPILLS: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Extinguish any ignition sources.

KEEP OUT OF REACH OF CHILDREN



K109



DURA PATCH

Roof Cement

- Use on asphalt built up roofing, composition, felts, metal, concrete, or masonry.
- Forms a durable waterproof surface.
- Rubber added for flexibility and crack resistance.
- Will outlast plastic roof cements.

Warning!

Combustible liquid and vapor.
Harmful or fatal if swallowed.

Dura Patch is a high quality, long lasting, non-asbestos fibered asphalt roof cement. Butyl rubber is added to give the cement flexibility and help it to resist cracking. This easily trowelable cement will remain pliable for many years as it forms a durable, weatherproof seal. Dura Patch can be used on asphalt built up roofs, composition, metal, masonry, or concrete surfaces. MEETS ALL THE REQUIREMENTS OF ASTM SPECIFICATION D4586.

USES: Dura Patch can be used to repair splits, cracks, or blisters in asphalt or composition roofing. Use it to adhere 90# granulated roofing paper. It can be used for sealing gutters, skylights, copings, vents, chimneys, roof fans, and to fasten loose shingles. It can be used to adhere or fix flashings.

PREPARATION: Surfaces to be coated must be clean and dry. Remove all dirt, dust, debris, or any other foreign matter by using a stiff brush, forced air, or hosing off the roof. Remove rust with a wire brush. If using on metal roofs securely attach any loose panels before using the roof cement.

APPLICATION: Apply with a trowel or putty knife. Trowel material firmly in place making sure all splits or voids are filled. The flashing cement should be finished to a feathered edge. For a stronger and longer lasting repair, first apply a layer of Dura Patch, then imbed glass fabric being careful to thoroughly saturate the fabric. The glass fabric should be laid flat, but not stretched. Then apply another layer of Dura Patch over the fabric. The Dura Patch should extend beyond the fabric for both coats. Under certain conditions, mainly hot, humid days, asphalt coatings or cements can dry brown or with brown spots streaks or spots. This phenomenon is known as browning. This condition will not effect the performance or life expectancy or asphalt coatings or cements.

COVERAGE: Approximately 8 gallons per 100 square feet depending on porosity of surface and type of repair being done.

RESTRICTIONS: For exterior use only. Do not thin. Do not use where material might come in contact with potable water. Do not use on wood surfaces or slate shingles. Do not use over coal tar or silicone. Do not use with PVC film. Do not use on single ply EPDM rubber or plastic membranes. Do not heat over direct flame. In cold weather it is advisable to store material in a warm location prior to use.

ATTENTION! Since empty containers contain product residue (vapors or liquid), all labeled hazardous precautions must be observed. Do not reuse empty pail. Dispose of empty containers in accordance with all applicable local, state, and federal regulations.

CLEAN UP: Tools and equipment: mineral spirits. Skin: waterless hand cleaner.

V.O.C.: 300 grams/liter maximum. Do not thin.

Kayline Company
P.O. Box 603207, Cleveland, Ohio 44103-0207
phone: 216-566-9858 (800-426-5820)
fax: 216-566-1228