

P.O. Box 603207
Cleveland, Ohio 44103-0207
(216) 566-9858
(800) 426-5820
FAX: (216) 566-1228



Maintenance Chemicals
Janitorial Supplies
Long Life Lighting
Lighting Fixtures
Water Treatment

K199 NON SKID COATING

DESCRIPTION:

Single part enamel, with integrated grit, provides a durable coarse non-slip surface. A non-chlorinated rubber resin base allows this non-skid coating to be applied to new, as well as, old concrete. Recommended for surfaces requiring a tough, work-safe surface.

PRODUCT CHARACTERISTICS:

- Excellent sure footing even in wet areas - stairways, loading docks, catwalks, shower rooms, wheel chair ramps, entrance ways, etc.
- Recommended for indoor or outdoor use
- Resistant to alkali, detergents, acids, etc.
- Six colors available
- Apply to wood, concrete, steel, stone, etc.

METHOD OF APPLICATION:

Surface should be structurally sound and free of water, oil or grease, loose paint, or other soils. Smooth concrete should be acid etched with 20% muriatic acid solution to insure good adhesion. Apply with brush, trowel, or notched squeegee. Once coated, surface may be back-rolled using a paint roller to both level and increase surface texture.

Two thin coats are recommended for maximum durability. Overnight dry between coats is recommended. Tools may be cleaned using rubber base thinner.

TECHNICAL DATA:

Specific Gravity	1.60
Color	Gray, Green, Red, Yellow, Black, Blue
Dry Time	5-6 hours
Flash Point (C.O.C.)	105 Degrees F
Coverage	100sq. ft/gallon

DURING APPLICATION, EXTINGUISH ALL FLAMES, INCLUDING PILOT LIGHTS, AND HAVE ADEQUATE VENTILATION. DO NOT USE IN CLOSED AREA.

AVAILABLE IN-- 5 GALLON AND 1 GALLON CONTAINERS

Over 100 Years of Excellence