

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I - PRODUCT IDENTIFICATION

Product Name: Air Duster

Product Number: T30

Product Type: AEROSOL

Distributor's Name: KAYLINE COMPANY

Distributor's Address: P.O. Box 603207, Cleveland, OH 44103

D.O.T. Proper Shipping Name: 1,1-Difluoroethane, R-152A, 2.1, UN1030, DOT-SP 11516

Formula: Proprietary

Date Prepared: 12/28/07

Emergency Phone: (800) 535-5053

Information Phone: (216) 566-9858

HMIS Rating (Based on Aerosol Conc.):

0-Minimal 1- Slight 2- Moderate

3- Serious 4- Extreme

HEALTH: 1 FIRE: 4 REACTIVITY: 1

Personal Protection : B

SECTION II - INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV	OTHER LIMITS
Difluoroethane	75-37-6	100	NO	NO	NO	N/E	N/E	1000 ppm

SECTION III - PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:

Boiling Point: ~ -13° F

pH: N/A

Solubility In Water: 0.28 WT% @70°F

Appearance/Odor: Clear Colorless Liquefied Gas, Ethereal Odor

Vapor Density (Air=1): 2.4

Specific Gravity (H₂O=1): 0.909

Data Below Based On Total Contents:

Vapor Pressure of can (psig @70°F): 62.5

Total VOC (Volatile Organic Compound) %: 0%

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): -58°F

Flammability (as per USA Flame Projection Test): Non-Flammable Spray

Extinguishing Media: Foam, CO₂, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V - REACTIVITY DATA

Stability: Material stable, however, avoid open flames & exposure to high temperatures.

Hazardous Polymerization: Will not Occur.

Incompatibility: Incompatible with alkali or alkaline earth metals.

Hazardous Decomposition Products: Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces ,etc.) forming hydrofluoric acid and possibly carbonyl fluoride.

SECTION VI - STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 1 Aerosol.

SECTION VII - HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: Can cause frostbite, severe irritation, redness, tearing, and blurred vision.

Skin: Contact with evaporating liquid can cause frostbite.

Inhalation: May produce anesthetic effects and feeling of euphoria. Prolonged overexposure can cause rapid breathing, headache, dizziness, narcosis, unconsciousness, and death from asphyxiation, depending on concentration and time of exposure.

Ingestion: Liquid ingestion may cause frostbite. Aspiration hazard.

FIRST AID PROCEDURES:

Eyes: In case of contact, immediately flush with large amounts of running water for at least 15 minutes while holding upper and lower lids open. Call a physician.

Skin: In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician. Treat for frostbite if necessary by gently warming affected area. Wash contaminated clothing before reuse.

Inhalation: If high concentrations are inhaled, immediately remove to fresh air. Keep person calm. If not breathing, give artificial respiration. Call a physician.

Ingestion: Do not induce vomiting. Contact a physician immediately.

SECTION VIII - SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions. Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus if in a confined space or in conditions where vapors exceed the recommended exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits.

Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemical products.

SECTION IX - SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Use absorbent material to collect any excess material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.